

Vertical centrifugal pumps Typhoon

TY 25

- Inlet connections: 2" F
- Outlet connections: 1" 1/2 M
- Max. Flow rate: 25 m³/h
- Max. Delivery head: 16 mts
- Max Viscosity: 400 cps
- Temperature PP: -5°C +65°C
- Temperature PVDF: -20°C +90°C



PP



PVDF


SPECIFIC GRAVITY TABLE

L = 1,5 Kw	M = 2,2 Kw	H = 3 Kw
up to 1, 2	up to 1,5	up to 1,9

MOTOR SPECIFICATION

SIZE	Kw	DESIGN
IEC 90	1,5	B5
IEC 90	2,2	B5
IEC 100	3	B5


DIMENSIONS



A	B	C	D	E	F	G	H	I	M	N	O	P
* 194	25	100	360	121	178	61	300	310	150	250	Ø199	

*Depend on the manufacturer

PERFORMANCE



The curves and performance values refer to pumps with free delivery outlet with water at 20 °C, and two poles motor 50 Hz. These data may vary according to the construction materials and hydraulic conditions.

COMPOSITION

MODEL	CASING	O RING	LENGTH mm	CONNECTIONS	PUMP DESIGN	MOTOR VERSION
TY025	P = PP K = PVDF	D = EPDM V = VITON	500 800 1000 1250	1 = BSP STD 2 = FLANGED	L = LOW DENSITY M = MEDIUM DENSITY H = HIGH DENSITY	IE = IEC FLANGE